

TECHNICAL DATA SHEET

M&C

SR25.2

Peristaltic pump CAPACITY 0.30 NI/H LIQUID PRESS 200MBAR TO 2.2 BAR POWER 115/230V 50/60HZ CONNECTION DN 4/6

PRODUCT PHOTO



General Information

Pump Type	Peristaltic pump
-----------	------------------

Performance Data

Capacity (Liquid)	0.30 NI/h
Pressure Range Minimum	200 mbar abs.
Pressure Range Maximum	2.2 bar abs.
Rotational Speed	5 rpm

Electrical Data

Power Supply Voltage	115/230 V
Power Supply Frequency	50/60 Hz
Protection Rating	IP10 EN 60529
Cable Length	700 mm

Mechanical Data

Tube Connection Size	DN 4/6
----------------------	--------

Materials

Tubing Material	Novoprene
Pump Head Material	PVDF

TECHNICAL DATA SHEET

M&C

SR25.2

Peristaltic pump CAPACITY 0.30 NI/H LIQUID PRESS 200MBAR TO 2.2 BAR POWER 115/230V 50/60HZ
CONNECTION DN 4/6

Installation

Method of Mounting	Attached to a front plate
--------------------	---------------------------

Operating Conditions

Ambient Temperature Minimum	0 °C
Ambient Temperature Maximum	+50 °C
Sample Temperature Minimum	0 °C
Sample Temperature Maximum	+60 °C

Storage Conditions

Storage Temperature Minimum	-10 °C
Storage Temperature Maximum	+60 °C

Request this product

<https://jaescompany.com/product.php?productid=154311>