

TECHNICAL DATA SHEET

SCHNEIDER ELECTRIC

A9N26924

Auxiliary contact

PRODUCT PHOTO



Electrical Characteristics

[Uc] control circuit voltage	24...415 V AC 50/60 Hz; 24...130 V DC
[In] Rated Current	3 A at 380...415 V, AC 50/60 Hz
[In] Rated Current	6 A at 220...240 V, AC 50/60 Hz
[In] Rated Current	1 A at 130 V, DC
[In] Rated Current	1.5 A at 60 V, DC
[In] Rated Current	2 A at 48 V, DC
[In] Rated Current	6 A at 24 V, DC

Configuration

Signal Contacts Composition	1 C/O
-----------------------------	-------

Compliance

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA, KEMA, LCIE, ASTA

Mechanical

Support de montage	Rail DIN
--------------------	----------

Dimensions

Hauteur	85,3 mm
largeur	9 mm
Profondeur	73,5 mm

TECHNICAL DATA SHEET

SCHNEIDER ELECTRIC

A9N26924

Auxiliary contact

Environment

Degré de protection IP	IP20 conforming to EN/CEI 60947-5-1
Degré de pollution	3 conforme à EN/CEI 60947-5-1
Température de l'air ambiant en fonctionnement	-25...50 °C
Température de l'air ambiant de stockage	-40...85 °C

Commercial

Garantie	18 mois
----------	----------------

Request this product

<https://jaescompany.com/product.php?productid=157520>