TECHNICAL DATA SHEET

Harting

09 15 000 6103

crimp contact

PRODUCT PHOTO



Identification

Series	**Han D®**
Type of contact	**Crimp contact**

Version

Termination method	**Crimp termination**
Gender	**Male**
Manufacturing process	**Turned contacts**

Technical characteristics

Conductor cross-section	**0.5 mm²**
Conductor cross-section [AWG]	**AWG 20**
Rated current	**≤ 10 A**
Contact resistance	**≤ 3 mΩ**
Stripping length	**8 mm**
Mating cycles	**≥ 500**

Material properties

Material (contacts)	**Copper alloy**
Surface (contacts)	**Silver plated**
RoHS	**compliant with exemption**
RoHS exemptions	**6(c): Copper alloy containing up to 4 % lead by weight**
ELV status	**compliant with exemption**
China RoHS	**50**

TECHNICAL DATA SHEET

Harting

09 15 000 6103

crimp contact

Material properties (continued)

REACH Annex XVII substances	**Not contained**
REACH ANNEX XIV substances	**Not contained**
REACH SVHC substances	**Yes**
REACH SVHC substances	**Lead**
ECHA SCIP number	**b51e5b97-eeb5-438b-8538-f1771d43c17d**
California Proposition 65 substances	**Yes**
California Proposition 65 substances	**Lead**

Specifications and approvals

Specifications	**IEC 60664-1**
Specifications	**IEC 61984**

Commercial data

Packaging size	**100**
Net weight	**0.6 g**
Country of origin	**Germany**
European customs tariff number	**85366990**
GTIN	**5713140021822**
eCl@ss	**27440204 Contact for industrial connectors**
ETIM	**EC000796**
UNSPSC 24.0	**39121522**

Technical attributes

Insulation diameter	**3.2 mm**

Request this product

https://jaescompany.com/product.php?productid=180391