TECHNICAL DATA SHEET

SIEMENS

3RT1276-6AB36

CONTACTOR.S.V.S12 250KW CONV.23/26UC

PRODUCT PHOTO



General Information

Product brand name	**SIRIUS**
Product type designation	**3RT12**

General Technical Data

Size of contactor	**S12**

Product Extension

Function module for communication	**No**
Auxiliary switch	**Yes**

Power Loss

Power loss at AC in hot operating state for rated value of the current	**96 W**
Power loss at AC in hot operating state per pole for rated value of the current	**32 W**

Isolation

Maximum permissible voltage for safe isolation between coil and main contacts according to	**690 V**

Shock Resistance

Shock resistance at rectangular impulse at AC	**8,5g / 5 ms, 4,2g / 10 ms**
Shock resistance at rectangular impulse at DC	**8,5g / 5 ms, 4,2g / 10 ms**
Shock resistance with sine pulse at AC	**13,4g / 5 ms, 6,5g / 10 ms**

TECHNICAL DATA SHEET

SIEMENS

3RT1276-6AB36

CONTACTOR.S.V.S12 250KW CONV.23/26UC

Shock Resistance (continued)

Shock resistance with sine pulse at DC	**13,4g / 5 ms, 6,5g / 10 ms**

Standards

Reference code according to IEC 81346-2	**Q**

Compliance

Substance Prohibitance (Date)	**05/01/2012**

Ambient Conditions

Installation altitude at height above sea level maximum	**2 000 m**

Request this product

https://jaescompany.com/product.php?productid=20977