TECHNICAL DATA SHEET

SIEMENS

6GK1102-4AA00

optical link module - SIMATIC - 3 ITP ports; 2 optical fibre ports;



Interfaces	
ITP Ports	**3**
Optical Fibre Ports	**2 BFOC**

Electrical Data	
Operating Supply Range	**18 to 32 V DC SELV**
Typical Current at 24 V	**160 mA**
Maximum Current at 24 V	**280 mA**

Performance	
Ethernet Transmission Rate	**10 Mbps**

Environmental	
Ingress Protection	**IP30**
Operating Temperature	**0 to +60 deg C**
Storage Temperature	**-40 to +80 deg C**
Relative Humidity	**10 to 90%, non-condensing**

Network Topology	
Maximum ITP Segment Length	**100 m**
Maximum Fiber Segment Length (50/125 µm)	**2600 m**
Maximum Fiber Segment Length (62.5/125 µm)	**3100 m**

Request this product https://jaescompany.com/product.php?productid=237107

TECHNICAL DATA SHEET

SIEMENS

6GK1102-4AA00

optical link module - SIMATIC - 3 ITP ports; 2 optical fibre ports;

Optical Specifications	
Optical Output Power (50/125 µm)	**-22.0 to -16.2 dBm**
Optical Output Power (62.5/125 µm)	**-19.0 to -12.4 dBm**
Minimum Optical Input Power	**-33.0 dBm**

Request this product https://jaescompany.com/product.php?productid=237107