TECHNICAL DATA SHEET

SIEMENS

6GK1503-2CB00

MODULE



Technical Data	
Transfer rate / with PROFIBUS	**9.6 kbit/s ... 12 Mbit/s**
Transfer rate / with PROFIBUS PA	**45.45 kbit/s**

Electrical Data	
Supply voltage / at DC / rated value	**24 V**
Supply voltage / at DC	**18.8 ... 28.8 V**
Consumed current / at DC / at 24 V / maximum	**0.2 A**
Operating voltage / of the signaling contacts / at DC / rated value	**24 V**
Operational current / of the signaling contacts / at DC / maximum	**0.1 A**

Physical Data	
Net Weight	**0.411 Kg**
Width	**39.5 mm**
Height	**112 mm**
Depth	**74.5 mm**

Interfaces	
Design of the optical interface / for fiber optic cable	**BFOC port**

Request this product https://jaescompany.com/product.php?productid=40635

TECHNICAL DATA SHEET

SIEMENS

6GK1503-2CB00

MODULE

Optical Properties	
Attenuation for glass FOC with 50/125 µm / at 3 dB/km / maximum	**10 dB**
Attenuation for glass FOC with 62.5/125 µm / at 3.5 dB/km / maximum	**12 dB**

Request this product https://jaescompany.com/product.php?productid=40635