

3351-0032-572452 MULTIWAY BALL VALVE
 TYPE : MW-4X SERIE: 2 IND.-DATE:
 SPEC.FEAT.: TYPE-IND.:
 CONSTRUCTION: 120420244 CS/BRS-BRS-FPM SERIENIND:
 DN inch: 1 1/4 SPEC.DESIGN: 00000 WEIGHT TOTAL: 9,500 /KG

CONNECTION 1 : M6 G 1 1/4 PRESSURE NOMINAL : DIN 50
 CONNECTION 2 : M6 G 1 1/4 ALLOW. WOP / PS : 50,0 BAR
 CONNECTION 3 : M6 G 1 1/4 PRESSURE TEST F : HYD 75,0 BAR
 CONNECTION 4 : M6 G 1 1/4 PRESSURE TEST D : AIR6 BAR
 VALVEBORE : CLOSING DIRECTION : R90
 F-to-F acc. to : OVERALL LENGTH : 0,0
 SURF/TREATM : ALUMINUM DA ACC. NAN 1215 ALLOW.WORKTEMPMAX / TS : 200 C
 SECTIONAL/DWG : 3D0360 ALLOW.WORKTEMPMIN / TS : -10 C
 ASSEMBLYDWG : 3D0746 ASSEMBLY ACC.TO :
 TOPWORKS DWG. : DIN ISO PLATE :
 LEVER SIZE :

LEVEL	ITEM	DESIGNATION	REF	QTY	UN	MATERIAL
1	0001	BODY	561908	1,00	ST	0.7040 / A 536 GR. 60-40-18
.2	0002	CONNECTING SOCKET	560354	4,00	ST	1.0718 K / A108 GR.12L13
.2	0005	PROTECTIVE CAP	203414	4,00	ST	PE / SOFT /
.2	0006	STOP DISK	560877	1,00	ST	1.0037 /
.2	0007	LOCKING PIECE	560347	1,00	ST	1.0570.01 / A694 GR.F52 (1174)
.2	0009	GROOVED PIN 8 x 16	100764	1,00	ST	6.8 EN ISO 898-1 /
.2	0010	CIRCUP. SNAP RING	100539	1,00	ST	SPRING STEEL / SPRING STEEL
.2	0090	NAME PLATE	151713	1,00	ST	1.4301 /
.2	0031	BALL SEAT	560716	4,00	ST	FPM / MS /
.2	0032	O-RING 34 x 3	150126	4,00	ST	FPM 80+-5 SHORE /
.2	0033	O-RING 42 x 3	150130	2,00	ST	FPM 80+-5 SHORE /
.2	0034	O-RING 44 x 3	150131	4,00	ST	FPM 80+-5 SHORE /
.2	0035	O-RING 86 x 4	150151	1,00	ST	FPM 80+-5 SHORE /
.2	0036	BOURDON TUBE	560363	4,00	ST	2.0335.30 /
.2	0037	BUSHING	560303	2,00	ST	PTFE SPEZ.FIRMENBEZ. /
1	0021	VALVE STEM	560346	1,00	ST	CUZN40PB2 R360 /
1	0050	WRENCH	589029	1,00	ST	ALMGS11 F31 /