



10	OIL SEAL	NBR	3	S3745B					
13	SPACER RING	S45C	1						
12	BEARING	SUJ	3	#22206					
11	BEARING	SUJ	1	#22207					
10	ROTOR STOP	S45C	2						
9	GEAR	S45C	4						
8	SHAFT (2)	S45C	1						
7	SHAFT (1)	S45C	1						
6	SIDE PIECE	FC250	3						
5	SIDE PIECE	FC250	1		19				
4	COVER (3)	FC250	1		18	O-RING	NBR	2 AN6230 #32	
3	COVER (2)	FC250	1		17	COVER (4)	SS400	1	
2	COVER (1)	FC250	1		16	O-RING	NBR	1 G-65	
1	CASING	FC250	1		15	SEAL COVER	S45C	1	
NO	NAME	MAT	QUA	NOTE	NO	NAME	MAT	QUA	NOTE

PUMP SPECIFICATIONS	
TYPE FORM	GR-CH602L
QUANTITY	520 l/min
SUCTION PRESS	-0.5 kg/cm ² g
DISCHARGE PRESS	5 kg/cm ² g
SUCTION BORE	4 B
DISCHARGE BORE	4 B
SPEED	960 rpm
MOTOR OUT PUT	15 kW
LIQUID & TEMP	
VIEW FROM DRIVE SIDE	CW
ACCESSORY	

USER			
TYPE FORM	GR-CH602L	THIRDANG.PROJ.	
MFG. No.	92038	SCALE	N.T.S
PRODUCTION No.		Q'TY	1
ORDER No.	91-00493-1.	DWN.	FEB. 14. 1992 S. TAKAHASHI
SERIAL No.		APPD.	
ITAYA TYPE GEAR PUMP		DWG. No.	
MUSASHINO Co., Ltd.		M-15700	